

# Specification Sheet

## *Scheda tecnica*

### WLS-50L

<b>Thermostat</b> <i>Termostato</i>	Dixell	<b>Temperature Range(°C)</b> <i>Range temperatura</i>	0~+5°C
<b>Climate temperature</b> <i>Temperatura ambiente</i>	25°C RH60%	<b>Climate class</b> <i>Classe climatica</i>	3
<b>Power (W)</b> <i>Potenza</i>	300	<b>LED Lights Power</b> <i>Potenza luce LED</i>	8
<b>Compressor Brand</b> <i>Marchio compressore</i>	Huayi	<b>Compressor Power (hp)</b> <i>Potenza compressore</i>	1/5+
<b>Voltage(V/Hz/Ph)</b> <i>Voltaggio</i>	220-240/50/1	<b>Compressor Model</b> <i>Modello compressore</i>	HYE125MHU
<b>Rated Current (A)</b> <i>Corrente nominale</i>	2	<b>Capacity (L)</b> <i>Capacità</i>	50
<b>Net weight (kg)</b> <i>Peso netto</i>	38	<b>Gross Weight (kg)</b> <i>Peso lordo</i>	53
<b>Exterior Dimensions (mm)</b> <i>Dimensioni esterne</i>	1175*430*310	<b>Interior Dimensions (mm)</b> <i>Dimensioni interne</i>	724*378*227
<b>Foaming Material</b> <i>Materiale coibentante</i>	C5H10	<b>Insulation thickness (mm)</b> <i>Spessore Coibentazione</i>	30
<b>Refrigerant</b> <i>Gas Refrigerante</i>	R600a	<b>Refrigerant Amount (g)</b> <i>Quantità gas</i>	50g
<b>Cooling Method</b> <i>Tipo refrigerazione</i>	Static/Statico	<b>Defrost Method</b> <i>Sbrinamento</i>	AIR DEFROST/ Ad aria
<b>Wood Packing Dimensions (mm)</b> <i>Dimensioni imballo</i>	1247*490*441	<b>GN pan QTY (pcs)</b> <i>Qtà bacinelle</i>	4xGN1/3 20mm